

# Index

Bold type is used for contributors to this volume. The suffix e indicates editorial comment; c, a conference report; r, a book review. Abbreviations: fr, fibre-reinforced; grc, glass-reinforced cement; lw, light-weight; pfa, pulverised fuel ash.

Aardelite, 160–7  
 accelerated tests  
   ageing of pfa/grc composites, 6–8, 9  
   pfa coarse aggregate concrete, 166–7  
   sulphate attack of asbestos cement pipes, 170, 171  
 acrylic resins, 219, 221  
 adhesion, see shear bond strength  
 adhesives, polymeric, 219–20 (see also epoxy resins)  
 ageing  
   casting delay, 109–13  
   effect on strength of copper fr cement, 195, 196  
   epoxy resins, 236  
   pfa/grc composites, 5, 7–9  
 aggregates  
   coarse pfa, 159–67  
   recycled, 271–2r  
**Al-Adieb, A.** and **Matti**, 'Sulphate attack on asbestos cement pipes', 169–76  
 Altofts canal bridge, 230, 231  
 asbestos cement pipes  
   sulphate attack, 169–76  
 ASTM Standards, 62r  
 axial stress in ferrocement, 151–7  
 bamboo fr concrete, 139r  
**Barr, B.I.G.**, Liu and Watkins, 'Mode II fracture of reinforced concrete materials', 93–101  
 beams  
   model for fracture under in-plane shear, 39–47  
   natural fr concrete, 11–19  
   torsional behaviour of reinforced concrete, 261–7  
 bending strength  
   pfa/grc composites, 5, 6–9  
 bending stress in ferrocement, 151–7  
**Bentur, A.**, Mindess and Diamond, 'Pull-out processes in steel fibre reinforced cement', 29–37  
**Bijen, J. M. J. M.** and van der Wegen, 'Properties of concrete made with three types of artificial PFA coarse aggregates', 159–67

Birmingham University Mining and Metallurgy Department, 234, 237  
 Blackburn road viaduct, 228, 230  
 blending of polymer concrete, 50–2  
 bolted joints with epoxy resin adhesives, 222, 227, 235, 239, 257  
 bond strength  
   oil-saturated concrete, 117–30  
   steel fibres, 86–7  
   tests, 115–16  
 bonding  
   characteristics of oil-saturated concrete, 115–30  
   in cellulose fr cement, 73–9  
   interpretation of pull-out tests in steel fr cement, 29–30  
   maximum shear stress in fibre-matrix bond, 79–80  
 book reviews, 59–62r, 137–40r, 206–7r, 271–4r  
 bridges  
   repair with epoxy resins, 228–31  
   repair with styrene-butadiene latex concrete, 241–6  
   segmental construction using epoxy resins, 221, 225–9, 230, 257–8  
 Brinsworth railway bridge, 228, 230  
 British Standards  
   test methods for resin compositions, 249–52  
**Bruhwiller, E.**, 'Effect of compressive loads on the tensile strength of concrete at high strain rates', 103–108  
 building boards  
   glass fr cement based, 1e, 3–10  
 Building Codes  
   reinforced concrete, 60r  
   structural plain concrete, 60r  
   thermosetting plastics, 231

calcium aluminosulphates, 7–8, 170, 173  
 calcium hydroxide (lime), 8–10, 170  
 Cambridge University New Museums Laboratories, 235, 239  
 carbonation of pfa/grc composites, 8–10  
 casting process  
   effect of delay on workability and strength, 109–13  
   effect of direction on stress-strain curves 87–8, 91–2  
 cement composites  
   bonding in cellulose fr, 73–9  
   compacted copper fr, 193–7  
   fracture mechanics, 134–5c

glass fr, with added pfa, 3–10  
 hydraulic, 58r  
 pull-out processes in steel fr, 29–37  
 very high strength, 134–5c  
 cement slurry as retempering agent, 177–82  
 chemical resistance  
   epoxy resins, 259–60  
   polymer concrete, 231  
   resin composition standard, 251, 252  
 China, 268–70c  
 Choisy-le-Roi bridge, 225–6  
 coarse aggregates, pfa, 160–2  
   concrete containing, 159, 162–7, 215e  
 colour incorporation in polymer concrete, 52–3  
 compaction methods for polymer concrete, 52–3, 57  
 compression tests  
   compact, 99  
   inelastic deformation behaviour, 81–92  
   steel fr and stirrup reinforced concrete, 183–92  
 compressive strength  
   artificial pfa coarse aggregate concrete, 162–4  
   effect of casting delay, 112–13  
   latex modified concrete, 243  
   MOTEMA-acrylic concrete, 57  
   reinforced concrete columns, 186–92  
   resin composition standard, 250, 251, 252  
   steel fr concrete under high strain rates, 21–7, 28  
   untreated plain and superplasticised concrete, 178, 180–2  
 compressive toughness  
   steel fr concrete, 90–2  
 conferences and symposia  
   forthcoming, 63–8c, 141–7c, 208–14c, 275–80c, 282c  
   reports, 133c, 203–5c, 268–70c  
 construction techniques  
   current practice for concrete materials, 61–2r  
   in tropical developing countries, 137r  
   latex modified concrete, 244–6  
   with resins, 217–22, 225–31, 233–9  
 copper fr cement composite, 193–7  
 corrosion  
   chloride permeability of latex modified concrete, 243, 245  
   protection with epoxy coatings, 228, 231

- steel fr concrete and shotcrete, 149–50e  
sulphate attack of asbestos cement pipes, 169–76  
courses, 69, 148, 214, 281  
**Coutts, R. S. P.**, Morrissey and Grossman, 'Bond between cellulose fibres and cement', 73–80  
Coventry Cathedral, 234–5, 237  
cracking  
  asbestos cement pipes, 170, 171, 173, 175  
  at an early age, 199–201  
  at high strain rates, 106–8  
  ferrocement under combined axial and bending stress, 153–4  
  latex modified concrete, 242–3  
  modes, 39–40, 93–4  
  MOTEMA-acrylic concrete, 55–6  
  sisal twine reinforced concrete beams, 12–13, 14, 16, 17  
  steel fr cement paste in pull-out tests, 29–30, 31–7  
  steel fr reinforced concrete beams under torsion, 263–4, 265–6  
crane rail supports, 221–2, 258  
creep  
  artificial pfa coarse aggregate concrete, 166  
  MOTEMA-acrylic concrete, 55, 56  
  resin composition standard, 250, 251  
cryogenic conditions, 215e, 273r  
curing  
  epoxy resins, 253  
  latex modified concrete, 243, 245–6  
  methods for concrete, 207r  
deformation, see stress-strain characteristics  
deformation energy  
  reinforced concrete columns under compression, 186–7, 188  
  steel fr concrete under high strain rates, 26–7, 28  
density  
  resin composition standard, 250, 251  
design  
  current practice for concrete materials, 61–2r, 271r  
  grc, 268c  
  hazard protection, 61r  
  reinforced concrete slabs, 59–60r  
design life, see durability  
developing countries, 1e, 137r  
**Diamond, S.**, Bentur and Mindess, 'Pull-out processes in steel fibre reinforced cement', 29–37  
**Diaz, G.**, Kittl and Galleguillos, 'Properties of compacted copper fibre reinforced cement composite', 193–7  
drying shrinkage, see shrinkage  
ductility  
  reinforced concrete under compression, 183, 186–7  
  steel fr reinforced concrete beams, 261, 267  
durability  
  aggregates in concrete, 161  
  asbestos cement pipes, 169–76  
  building materials and components, 133–4c, 272–3r  
  concrete cracked at an early age, 199–201  
  design life of epoxy resin joints, 236, 259  
  latex modified concrete, 243–4  
  natural fr concrete beams, 19  
  pfa coarse aggregate concrete, 166–7  
  related to design, 71e, 139–40  
earthquakes, 272r, 273–4r  
elasticity modulus  
  latex modified concrete, 243, 244  
  resin composition standard, 250, 251  
epoxy resins, 218, 220  
  bridge construction, 221, 225–7, 228, 230  
  mortar and concrete applications, 253–9  
  repairs, 221–2, 227–31  
  structural applications, 233–9  
  test methods 249–52  
ettringite, 7–8, 170, 173, 176  
Evode offices, Stafford, 235, 239  
Exeter University science buildings, 234, 236, 238  
expansion  
  asbestos cement pipes, 171, 172, 175  
  pfa coarse aggregate concrete, 164–5  
expansive cements, 60–1r  
failure (see also fracture behaviour)  
  cellulose fr cement, 74–9  
  ferrocement under combined bending and axial stress, 153–7  
  in-plane shear of short beam, 44–6  
  oil-saturated concrete, 117  
  plain concrete at high strain rates, 104–108  
  reinforced concrete columns under compression, 185  
  steel fr reinforced concrete beams under torsion, 265–6  
**Faiyadh, F. I.**, 'Bond characteristics of oil-saturated concrete', 115–31  
ferrocement, 135–6c, 138r, 214  
iron/MOTEMA-acrylic concrete, 56, 57  
  under combined bending and axial loads, 151–7  
fibre content  
  effect on copper fr cement, 194–7  
  effect on torsional strength of reinforced beams, 261, 264–7  
fibre pull-out  
  failure mechanism in cellulose fr cement, 74–9  
  steel fr cement, 29–37  
fibre-reinforced composites, 206r, 207r, 268r, 282c  
fibre reinforcement, 59r, 138–9r  
  maximum shear stress in bond to matrix, 79–80  
  strengthening of twine reinforced concrete, 15–19  
fibre shape  
  effect on mechanical properties for steel, 89–90  
  effect on strength of fr composites, 22–7, 30, 31–7, 194–7  
fillers  
  incorporation in polymer concrete, 50, 52  
  iron powder, 56  
finite element studies of in-plane shear, 39–47, 94–6  
flexural strength  
  asbestos cement pipes after sulphate attack, 171–3, 174  
  latex modified concrete, 243  
  MOTEMA-acrylic concrete, 56–7  
  resin composition standard, 250, 251, 252  
  sisal twine reinforced concrete beams, 12–19  
flooring  
  epoxy coated, 255  
  mosaic backed with epoxy mortar, 254, 256  
  resin based industrial, 220, 255, 256  
fracture behaviour  
  failure process in cellulose fr cement, 74–5, 78–9  
  LEFR modelling for short beam shear, 39–46  
  polypropylene and steel fr concrete shear, 93–100  
fracture mechanics of cement composites, 134c  
fracture strength  
  copper fr cement, 194–7  
fracture toughness  
  polypropylene fr concrete, 97–8, 99  
  short concrete beam under in-plane shear, 46  
  steel fr concrete, 98–100  
fuel ash, see pulverised fuel ash  
**Galleguillos, E.**, Kittl and Diaz, 'Properties of compacted copper fibre reinforced cement composite',

- 193-7  
 Gartnavel General Hospital, Glasgow, 235, 239  
 Glasgow Airport terminal building, 234, 237  
 glass fr cement (grc), 1e, 268c  
   effect of pfa addition, 3-10  
 glass fr concrete, 138r  
**Grossman, P. U. A.**, Morrissey and Coutts, 'Bond between cellulose fibres and cement', 73-80  
 grouting  
   epoxy resin based, 221-2, 235, 239, 258, 259  
   polyester based, 221-2  
   techniques, 206-7r
- Hartwich, K.** and Rostasy, 'Compressive strength and deformation of steel fibre reinforced concrete under high rate of strain', 21-8  
**Hatanaka, S.**, Kosaka and Tanigawa, 'Lateral confining stresses due to steel fibres in concrete under compression', 81-92  
 hazards, see under safety  
 hooked steel fibre reinforcement  
   compressive strength under high rates of strain, 22-7  
   interpretation of pull-out tests, 30, 32, 34, 35-7, 81-7  
   mechanical properties, 89-90  
 housing systems, prefabricated, 1e  
 hydraulic cements, 59r
- impact strength  
   pfa/grc composites, 5-9  
 inelastic deformation of concrete, 81-92  
 iron (see also ferrocement)  
   incorporation with MOTEMA-acrylic concrete, 56, 57
- joints bonded with epoxy resins, 220-2, 234, 235-9
- Kittl, P.**, Galleguillos and Diaz, 'Properties of compacted copper fibre reinforced cement composite', 193-7  
**Koblischek, P. J.**, 'MOTEMA - acrylic concrete for machine tool frames', 55-7  
**Kosaka, Y.**, Tanigawa and Hatanaka, 'Lateral confining stresses due to steel fibres in concrete under compression', 81-92  
**Kreis, R.**, 'Short curing times for the polymer concrete', 49-54  
**Kuhlmann, L. A.**, 'Latex modified concrete for the repair and rehabilitation of bridges', 241-7
- laminates, 206r  
 latices, polymeric, 219-20, 221-2, 241-6  
 lightweight concrete  
   marine applications, 215e  
   with artificial pfa aggregates, 159, 162-7  
**Lim, T. Y.** and Mansur, 'Torsional behaviour of reinforced fibre concrete beams', 261-7  
 lime, free, 8-10, 170  
**Liu, K. L. W.**, Barr and Watkins, 'Mode II fracture of fibre reinforced concrete materials', 93-101  
**Liu, K. L. W.** and Watkins, 'A finite element study of the short beam test specimen under mode II loading', 39-47  
 Lloyds building, London, 234, 237, 239  
 Lytag, 160-7
- Majumdar, A. J.** and Singh, 'The effect of pfa addition on the properties of grc', 3-10  
**Mangat, P. S.** and Motamedi Azari, 'Influence of steel fibre and stirrup reinforcement on the properties of concrete in compression members', 183-92  
**Mansur, M. A.** and Lim, 'Torsional behaviour of reinforced fibre concrete beams', 261-7  
**Mansur, M. A.** and Paramasivam, 'Ferrocement under combined bending and axial loads', 151-8  
 marine applications, 215e  
 mass concrete pours, 207r  
**Matti, M. A.** and Al-Adeeb, 'Sulphate attack on asbestos cement pipes', 169-76  
 microstructure  
   pfa/grc composites, 7  
   steel fr cement paste, 29-30, 31-7  
**Mindess, S.**, Bentur and Diamond, 'Pull-out processes in steel fibre reinforced cement', 29-37  
 mixing process for polymer concrete, 49-54  
 Mode I fracture, 99, 100  
 Mode II fracture  
   polypropylene and steel fr concrete, 93-100  
   short beam failure, 39-47  
 models, theoretical  
   failure in fr cements, 75-6  
   fracture of cement composites, 134-5c  
   shear fracture of short beams, 39-47
- modulus of elasticity, see elasticity  
 modulus  
 modulus of rupture  
   bending of pfa/grc composites, 5, 6, 7, 9  
   steel fr reinforced concrete beams, 263  
**Morrissey, F. E.**, Coutts and Grossman, 'Bond between cellulose fibres and cement', 73-80  
 mortars, polymer, 221, 253  
**Motamedi Azari, M.** and Mangat, 'Influence of steel fibre and stirrup reinforcement on the properties of concrete in compression members', 183-92  
 MOTEMA-acrylic concrete, 55-7  
 motorways, see bridges, road surfacing  
 moulds for polymer concrete, 52, 53  
**Mwamila, B. L. M.**, 'Natural twines as main reinforcement in concrete beams', 11-19
- Neffgen, B.**, 'Epoxy resins in the building industry - 25 years of experience', 253-60  
 Nether Edge Hospital, Sheffield, 234, 238-9  
 Niro Atmizer, 160-2
- O'Brien, T.**, 'Resins in construction: feedback from structural applications', 233-9  
 oil-saturated concrete, 115-30
- Paramasivam, P.** and Mansur, 'Ferrocement under combined bending and axial loads', 151-8  
 plain concrete  
   Building Code requirements, 60r  
   effect of casting delay, 109-13  
   effect of high strain rates, 23-8, 104-108  
   inelastic deformation under triaxial compression, 81, 82-4  
   model for fracture of short beams, 39-47  
   retempering, 177-82  
   tensile strength at high strain rates under compressive loads, 103-108  
 plasticity  
   compacted copper fr cement, 195-6  
   pfa/grc composites, 5, 6, 7  
   reinforced concrete, 137-8r  
 polyester resins, 218-19, 220, 221, 222  
 polymer concrete  
   applications, 53-4, 215e  
   continuous mixing and pouring process, 49-53  
   modified with styrene-butadiene latex, 241-6

- MOTEMA-acrylic, 55-7  
 properties of epoxy concrete, 254  
 repairs with epoxy resin concrete, 222, 228, 230  
 polymers, 217-22 (see also epoxy resins, polymer concrete)  
 test methods, 249-60  
 polymethyl methacrylate, 50, 55  
 polypropylene fr concrete, 138-9r, 268c  
 fracture studies, 96, 97-8  
 polyurethane resins, 219  
 portland cement  
 matrix with added pfa, 1e, 3-10  
 steel fibre pull-out processes, 29-37  
 pot life of resin compositions, 250, 251  
 pozzolans, 203c (see also pulverised fuel ash)  
 precast concrete, 149e, 204-5c, 268c  
 bridge construction, 225-7  
 epoxy resin adhesive techniques, 233-9  
 polymer, 259-60  
 prefabricated housing systems, 1e  
 pull-out  
 bar in oil-saturated concrete, 115-30  
 fibre, see fibre pull-out  
 pulverised fuel ash (pfa), 269c, 273r  
 addition to grc, 1e, 3-10  
 artificial aggregate, 159-67  
 chemical analysis, 4  
 pumping methods, 207r  
 quality control, 207r  
 epoxy resin joints, 237  
 quartz in MOTEMA-acrylic concrete, 55-7
- Ravindrarajah, R. S.** 'Casting delay on workability and strength of concrete', 109-113
- Ravindrarajah, R. S.** and Tam, 'Retempering of plain and superplasticised concretes', 177-82
- Rawcliffe river bridge, 226, 229
- recycling of concrete, 271-2r
- reinforced concrete  
 Building Code requirements, 60r  
 corrosion protection with epoxy resins, 228  
 earthquake effects, 273-4r  
 plasticity theories, 137-8r  
 prestressing steel, 207r  
 slabs, 59-60r  
 torsional behaviour of steel fr beams, 261-7  
 repair techniques  
 reinforcement corrosion damage, 61r  
 road surfaces, 255-7  
 spontaneous disappearance of early cracks, 199-201  
 structural reinforced concrete, 204c  
 with polymer materials, 221-2, 227, 228-31, 241-6, 255-7, 258  
 value judgement, 71e  
 resin concrete, see polymer concrete  
 resins, 217-22 (see also epoxy resins, polymer concrete)  
 latex modified concrete, 241-6  
 test methods, 249-60  
 ribbed steel fibre reinforcement, 35-7  
 road surfacing  
 repairs with epoxy mortars, 255-7
- Rostasy, F. S.** and Hartwich, 'Compressive strength and deformation of steel fibre reinforced concrete under high rate of strain', 21-8
- rupture modulus, see modulus of rupture
- safety  
 design for hazard protection, 61r  
 devices in polymer concrete mixer and pourer, 51-2  
 epoxy resin processing, 259
- sandwich structures  
 epoxy resin mortar facade panels, 258  
 iron/MOTEMA-acrylic concrete, 57  
 Scammonden bridge, 227  
 self-regeneration of cracked concrete, 199-201  
 set-retarding of concrete, 109-13  
 shape of fibre, see fibre shape  
 shape of specimen  
 effect on stress-strain curves, 84, 86-91  
 Mode II tests, 93-6, 98, 99, 100  
 resin composition standards, 250-2
- Shaw, J. D. N.**, 'Resins in construction', 217-23
- shear bond strength  
 latex modified concrete, 243, 244  
 resin composition standard, 250, 251, 252
- shear strength  
 failure of short concrete beam, 44-7  
 shotcreting, 149e, 204-5c
- shrinkage  
 absence in epoxy resin joints, 236  
 compensation, 60-1r  
 latex modified concrete, 243, 244  
 pfa coarse aggregate concrete, 164-6  
 resin composition standard, 250-2
- Sims, F. A.**, 'Applications of resins in bridge and structural engineering', 225-32
- Singh, B.** and Majumdar, 'The effect of pfa addition on the properties of grc', 3-10
- sisal fibres  
 bond to cement, 73-9  
 sisal fr concrete, 11-19
- slag products, 137r, 203c, 269c, 273r
- slip  
 load-slip relation for oil-saturated concrete, 118-19, 121-2, 124
- slump, see workability
- Somerville College, Oxford, 234, 235, 238
- steel fr cement  
 pull-out processes, 29-37
- steel fr concrete, 138r, 149-50e, 204-5c, 268c  
 compressive properties, 183-92  
 compressive strength at high strain rates, 21-8  
 inelastic deformation under uniaxial compression, 84-9  
 in-plane shear fracture, 96-100  
 lateral confining stresses under compression, 81-2  
 torsional behaviour of reinforced beams, 261-7  
 twine reinforced, 15-19
- steel mesh reinforced concrete, see ferrocement
- stirrup reinforcement  
 effect on concrete under compression, 183-92  
 effect on torsional behaviour of steel fr concrete, 261-7
- storage of polymer concrete, 53
- straight steel fibre reinforcement  
 effect on compressive strength under high rates of strain, 22-7  
 interpretation of pull-out tests, 31-2, 33, 35-7
- strain rates, high, 21-8, 103-108
- stress intensity factor, 39-40, 96  
 determination, 40-4  
 polypropylene fr concrete, 97-8
- stress-strain characteristics  
 compressive and tensile loading at high strain rates, 104-107  
 ferrocement under combined bending and axial stress, 153-7  
 oil-saturated concrete in pull-out tests, 119, 123  
 pfa/grc composites, 6, 8  
 plain concrete under triaxial compression, 83-4, 85, 86  
 reinforced concrete under compression, 183-92  
 steel fr and plain concrete under high strain rates, 23-4, 25-7  
 steel fr concrete under uniaxial compression, 84-92
- styrene-butadiene latex, 219-20, 242  
 modified concrete, 241-6
- sugar factory floors, 255, 256
- sulphates  
 attack on asbestos cement pipes, 169-76



- content in pfa-grc composites, 7-8  
superplasticiser  
effect on workability and compressive strength, 109-13  
retempering agent, 177-82
- Swamy, R. N.**, 1e, 71e, 149-50e, 215e  
swelling, see expansion  
Sydney Opera House, 234, 235, 237-8
- Tam, C. T.** and Sri Ravindrarajah, 'Retempering of plain and superplasticised concrete', 177-82
- Tanigawa, Y.**, Kosaka and Hatanaka, 'Lateral confining stresses due to steel fibres in concrete under compression', 81-92  
temperature effects, 273r  
tensile strength  
concrete cracked at an early age, 199-201  
concrete under compressive loads at high strain rates, 103-108  
effect of shape of steel fibres, 89  
MOTEMA-acrylic concrete, 57  
pfa coarse aggregate concrete, 162, 164  
pfa/grc composites, 5, 6, 7, 8  
resin composition standard, 250, 251, 252  
sisal, 76  
tension stiffening and toughness of twine reinforced concrete, 13-15, 19  
tension tests  
at high strain rates, 103-108  
compact, 30-7  
test methods (see also accelerated tests, compression tests, tension tests)  
bond strength, 115-16  
resin compositions, 249-52  
thermal properties  
lw concrete, 215e  
resin compositions, 250-2
- Tillyer, R. B.**, 'Resin compositions in the construction industry, development of test methods', 249-52
- Tinic, C.** and Bruhwiler, 'Effect of compressive loads on the tensile strength of concrete at high strain rates', 103-108
- torsion tests  
steel fr reinforced concrete beams, 261-7
- toughness  
fracture, 46  
steel fr reinforced concrete beams, 261, 267  
tension, 13-15, 19  
toughness index, 96-7  
steel fr concrete, 98, 99-100  
Trent river bridge, 226-7, 229  
tropical countries, 137r  
twines, 11-12  
concrete reinforcement, 12-19
- Urn Farm bridge, Leeds, 227, 229, 230
- van der Wegen, G. J. L.** and Bijen, 'Properties of concrete made with three types of artificial PFA coarse aggregates' 159-67
- Walton-upon-Thames swimming pool, 235, 239  
waste materials, 215e  
water  
effect on strength of copper fr cement, 195, 196  
retempering agent, 177-82  
water-cement ratio  
effect on stress-strain curves of plain concrete, 83-4, 86  
water reducing agent, see superplasticiser
- Watkins, J.** and Liu, 'A finite element study of the short beam test specimen under mode II loading', 39-47
- Watkins, J.**, Liu and Barr, 'Mode II fracture of fibre reinforced concrete materials', 93-101
- weathering  
epoxy resin joints, 236  
latex modified concrete, 246  
pfa/grc composites, 6, 7-9  
woodpulp fr cements, 73-4  
workability  
effect of casting delay, 109-13  
retempering agents to achieve, 177-82
- Young's modulus  
pfa coarse aggregate concrete, 162, 164  
pfa/grc composites, 5
- Zamorowski, W.**, 'The phenomenon of self-regeneration of concrete', 199-201